

Application No. 09/716,924

Page 2 of 18

IN THE CLAIMS

Please amend the claims of the present application as follows:

1. (canceled).

2. (canceled).

3. (currently amended) A method for controlling bandwidth allocations, the method comprising:

receiving bandwidth metrics for a destination site from a scheduler;

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value, wherein the reference control value is based upon a current limit value that is active during a measurement period of the bandwidth metrics;

allocating bandwidth based upon the control value; and

~~The method according to Claim 1, further comprising:~~

correlating the control value with the received bandwidth metrics.

4. (original) The method according to Claim 3, wherein the correlating step comprises:

generating a control sequence number corresponding to the control value.

5. (currently amended) A method for controlling bandwidth allocations, the method comprising:

receiving bandwidth metrics for a destination site from a scheduler;

Application No. 09/716,924

Page 3 of 18

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value;

allocating bandwidth based upon the control value; and

~~The method according to Claim 1, further comprising:~~

reading the a control sequence number associated with the measurement period, the control sequence number being included in a metric message that contains the bandwidth metrics.

6. (currently amended) A method for controlling bandwidth allocations, the method comprising:

receiving bandwidth metrics for a destination site from a scheduler;

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value;

allocating bandwidth based upon the control value; and

~~The method according to Claim 1, further comprising:~~

storing the control value, wherein the control value is indexed by the a control sequence number.

Application No. 09/716,924

Page 4 of 18

7. (currently amended) A method for controlling bandwidth allocations, the method comprising:  
receiving bandwidth metrics for a destination site from a scheduler;  
determining utilization associated with a destination site based upon the received bandwidth metrics;  
computing a difference between the determined utilization and a target utilization;  
computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;  
outputting a control value based upon a reference control value and the correction value, wherein the reference control value is stored in a control storage, and the reference control value having an index based upon a round-trip control time (RTCT), the RTCT being a time between sending of the control value and a subsequent control value; and  
allocating bandwidth based upon the control value.

~~The method according to Claim 1, wherein the reference control value in the outputting step is stored in a control storage, the reference control value having an index based upon a round-trip control time (RTCT), the RTCT being a time between sending of the control value and a subsequent control value.~~

8. (original) The method according to Claim 7, wherein the RTCT includes propagation delay, message transmit/receive delays, and message processing delay.

9. (original) The method according to Claim 7, further comprising:  
sending the control value on a predetermined interval, the index being based upon a ratio of the RTCT and the predetermined interval.

10. (original) The method according to Claim 7, further comprising:  
sending the control value to a traffic control processing logic that is located remotely from the scheduler.

Application No. 09/716,924  
Page 5 of 18

11. (currently amended) A method for controlling bandwidth allocations, the method comprising:  
receiving bandwidth metrics for a destination site from a scheduler;  
determining utilization associated with a destination site based upon the received bandwidth metrics;  
computing a difference between the determined utilization and a target utilization;  
computing a correction value based upon the difference between the determined utilization and the target utilization, and based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference, the correction value being associated with the destination site;  
outputting a control value based upon a reference control value and the correction value; and  
allocating bandwidth based upon the control value.

~~The method according to Claim 1, wherein the correction value in the step of computing the correction value is further based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference.~~

12. (currently amended) A method for controlling bandwidth allocations, the method comprising:  
receiving bandwidth metrics for a destination site from a scheduler;  
determining utilization associated with a destination site based upon the received bandwidth metrics;  
computing a difference between the determined utilization and a target utilization;  
computing a correction value based upon the difference between the determined utilization and the target utilization, and based upon a unity gain, the correction value being associated with the destination site;  
outputting a control value based upon a reference control value and the correction value; and  
allocating bandwidth based upon the control value.

Application No. 09/716,924  
Page 6 of 18

~~The method according to Claim 1, wherein the correction value in the step of computing the correction value is further based upon a unity gain.~~

13. (canceled).

14. (canceled).

15. (currently amended) A communication system for controlling bandwidth allocations, comprising:

a scheduler configured to generate bandwidth metrics for a destination site; and

a traffic control processing logic configured to receive the bandwidth metrics, the traffic control processing logic comprising,

a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics,

an error calculation module configured to compute a difference between the determined utilization and a target utilization,

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site, and

an adder configured to output a control value based upon a reference control value and the correction value, wherein the reference control value is based upon a current limit value that is active during a measurement period of the bandwidth metrics, the current limit value being received by the traffic control processing logic; and

a bandwidth control processor configured to perform bandwidth allocation based upon the control value; and

~~The system according to Claim 14, wherein the gain and filtering module generates a control sequence number corresponding to the control value.~~

16. (original) The system according to Claim 15, wherein the scheduler reads the control sequence number associated with the measurement period, the control sequence number being included in a metric message that contains the bandwidth metrics.

17. (original) The system according to Claim 15, wherein the traffic control processing logic further comprises:

a control storage configured to store the control value, the control value being indexed by the control sequence number.

18. (original) The system according to Claim 15, wherein the reference control value is stored in the control storage, the reference control value having an index based upon a round-trip control time (RTCT), the RTCT being a time between sending of the control value and a subsequent control value.

19. (original) The system according to Claim 18, wherein the RTCT includes propagation delay, message transmit/receive delays, and message processing delay.

20. (original) The system according to Claim 18, wherein the control value is sent to the traffic control processing logic on a predetermined interval, the index being based upon a ratio of the RTCT and the predetermined interval.

21. (currently amended) A communication system for controlling bandwidth allocations, comprising:

a scheduler configured to generate bandwidth metrics for a destination site; and

a traffic control processing logic configured to receive the bandwidth metrics, the traffic control processing logic comprising,

a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics.

Application No. 09/716,924

Page 8 of 18

an error calculation module configured to compute a difference between the determined utilization and a target utilization,

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site, and

an adder configured to output a control value based upon a reference control value and the correction value; and

a bandwidth control processor configured to perform bandwidth allocation based upon the control value; and

~~The system according to Claim 13, wherein the scheduler resides in a payload of a satellite and the traffic control processing logic is located remotely from the satellite.~~

22. (canceled).

23. (currently amended) A communication system for controlling bandwidth allocations, comprising:

a scheduler configured to generate bandwidth metrics for a destination site; and

a traffic control processing logic configured to receive the bandwidth metrics, the traffic control processing logic comprising,

a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics,

an error calculation module configured to compute a difference between the determined utilization and a target utilization,

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, and based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference, the correction value being associated with the destination site, and

an adder configured to output a control value based upon a reference control value and the correction value; and

Application No. 09/716,924  
Page 9 of 18

a bandwidth control processor configured to perform bandwidth allocation based upon the control value.

~~The system according to Claim 13, wherein the correction value is further based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference.~~

24. (currently amended) A communication system for controlling bandwidth allocations, comprising:

a scheduler configured to generate bandwidth metrics for a destination site; and

a traffic control processing logic configured to receive the bandwidth metrics, the traffic control processing logic comprising,

a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics,

an error calculation module configured to compute a difference between the determined utilization and a target utilization,

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, and based upon a unity gain, the correction value being associated with the destination site, and

an adder configured to output a control value based upon a reference control value and the correction value; and

a bandwidth control processor configured to perform bandwidth allocation based upon the control value.

~~The system according to Claim 13, wherein the correction value is further based upon a unity gain.~~

25. (canceled).

26. (canceled).



Application No. 09/716,924  
Page 10 of 18

27. (currently amended) A traffic control processing device for managing available bandwidth based upon bandwidth metrics from a scheduler, comprising:

a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics;

an error calculation module configured to compute a difference between the determined utilization and a target utilization;

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with a destination site;

an adder configured to output a control value based upon a reference control value and the correction value, wherein the reference control value is based upon a current limit value that is active during a measurement period of the bandwidth metrics, the current limit value being received by the traffic control processing logic; and

~~The device according to Claim 26, wherein the gain and filtering module generates a control sequence number corresponding to the control value.~~

28. (original) The device according to Claim 27, wherein the scheduler reads the control sequence number associated with the measurement period, the control sequence number being included in a metric message that contains the bandwidth metrics.

29. (original) The device according to Claim 27, wherein the traffic control processing logic further comprises:

a control storage configured to store the control value, the control value being indexed by the control sequence number.

30. (original) The device according to Claim 27, wherein the reference control value is stored in the control storage, the reference control value having an index based upon a round-trip control time (RTCT), the RTCT being a time between sending of the control value and a subsequent control value.

31. (original) The device according to Claim 30, wherein the RTCT includes propagation delay, message transmit/receive delays, and message processing delay.

32. (original) The device according to Claim 30, wherein the control value is sent to the traffic control processing logic on a predetermined interval, the index being based upon a ratio of the RTCT and the predetermined interval.

33. (currently amended) A traffic control processing device for managing available bandwidth based upon bandwidth metrics from a scheduler, comprising:  
a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics;

an error calculation module configured to compute a difference between the determined utilization and a target utilization;

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, and based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference, the correction value being associated with the destination site;  
and

an adder configured to output a control value based upon a reference control value and the correction value.

~~The device according to Claim 25, wherein the correction value is further based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference.~~

34. (currently amended) A traffic control processing device for managing available bandwidth based upon bandwidth metrics from a scheduler, comprising:  
a utilization module configured to determine utilization associated with a destination site based upon the received bandwidth metrics;

Application No. 09/716,924  
Page 12 of 18

an error calculation module configured to compute a difference between the determined utilization and a target utilization;

a gain and filtering module configured to compute a correction value based upon the difference between the determined utilization and the target utilization, and based upon a unity gain, the correction value being associated with the destination site; and

an adder configured to output a control value based upon a reference control value and the correction value.

~~The device according to Claim 25, wherein the correction value is further based upon a unity gain.~~

35. (canceled).

36. (canceled).

37. (currently amended) A computer-readable medium carrying one or more sequences of one or more instructions for controlling bandwidth allocations, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving bandwidth metrics for a destination site from a scheduler;

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value;

allocating bandwidth based upon the control value; and

~~The computer readable medium according to Claim 35, further comprising computer-executable instructions for causing the computer system to perform the steps of:~~

correlating the control value with the received bandwidth metrics.

38. (currently amended) A computer-readable medium carrying one or more sequences of one or more instructions for controlling bandwidth allocations, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving bandwidth metrics for a destination site from a scheduler;

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value;

allocating bandwidth based upon the control value; and

~~The computer readable medium according to Claim 35, further comprising computer-executable instructions for causing the computer system to perform the steps of:~~

generating a control sequence number corresponding to the control value.

39. (currently amended) A computer-readable medium carrying one or more sequences of one or more instructions for controlling bandwidth allocations, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

Application No. 09/716,924

Page 14 of 18

receiving bandwidth metrics for a destination site from a scheduler;  
determining utilization associated with a destination site based upon the received bandwidth metrics;  
computing a difference between the determined utilization and a target utilization;  
computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;  
outputting a control value based upon a reference control value and the correction value;  
allocating bandwidth based upon the control value; and

~~The computer-readable medium according to Claim 35, further comprising computer-executable instructions for causing the computer system to perform the steps of:~~

storing the control value, wherein the control value is indexed by the a control sequence number.

40. (currently amended) A computer-readable medium carrying one or more sequences of one or more instructions for controlling bandwidth allocations, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving bandwidth metrics for a destination site from a scheduler;  
determining utilization associated with a destination site based upon the received bandwidth metrics;  
computing a difference between the determined utilization and a target utilization;  
computing a correction value based upon the difference between the determined utilization and the target utilization, the correction value being associated with the destination site;  
outputting a control value based upon a reference control value and the correction value, wherein the reference control value is stored in a control storage, the

Application No. 09/716,924  
Page 15 of 18

reference control value having an index based upon a round-trip control time (RTCT),  
the RTCT being a time between sending of the control value and a subsequent control  
value; and

allocating bandwidth based upon the control value.

~~The computer readable medium according to Claim 35, further comprising  
computer-executable instructions for causing the computer system to perform the steps  
of:~~

~~wherein the reference control value in the outputting step is stored in a control  
storage, the reference control value having an index based upon a round-trip control  
time (RTCT), the RTCT being a time between sending of the control value and a  
subsequent control value.~~

41. (original) The computer readable medium according to Claim 40, wherein  
the RTCT includes propagation delay, message transmit/receive delays, and message  
processing delay.

42. (original) The computer readable medium according to Claim 40, further  
comprising computer-executable instructions for causing the computer system to  
perform the steps of:

sending the control value on a predetermined interval, the index being based  
upon a ratio of the RTCT and the predetermined interval.

43. (original) The computer readable medium according to Claim 40, further  
comprising computer-executable instructions for causing the computer system to  
perform the steps of:

sending the control value to a traffic control processing logic that is located  
remotely from the scheduler.

Application No. 09/716,924  
Page 16 of 18

44. (currently amended) A computer-readable medium carrying one or more sequences of one or more instructions for controlling bandwidth allocations, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving bandwidth metrics for a destination site from a scheduler;

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

computing a correction value based upon the difference between the determined utilization and the target utilization, and based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value; and

allocating bandwidth based upon the control value.

~~The computer-readable medium according to Claim 35, wherein the correction value in the step of computing the correction value is further based upon a split gain that specifies at least one of a first gain and a second gain based upon the computed difference.~~

45. (currently amended) A computer-readable medium carrying one or more sequences of one or more instructions for controlling bandwidth allocations, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving bandwidth metrics for a destination site from a scheduler;

determining utilization associated with a destination site based upon the received bandwidth metrics;

computing a difference between the determined utilization and a target utilization;

Application No. 09/716,924  
Page 17 of 18

computing a correction value based upon the difference between the determined utilization and the target utilization, and based upon a unity gain, the correction value being associated with the destination site;

outputting a control value based upon a reference control value and the correction value; and

allocating bandwidth based upon the control value.

~~The computer readable medium according to Claim 35, wherein the correction value in the step of computing the correction value is further based upon a unity gain.~~